

PROLONG

WARNING

Do not open container before reviewing application instructions, SDS and warnings.

Ventilation and protective equipment recommended. Do not ingest. Keep away from children.

REAL
SiO₂
TECHNOLOGY



PROTECT

NANOCERAMIC TECHNOLOGY



Renews and maintains the outer surface of Paint Pro, Paint Pro XD and Glass Pro.



Adds additional UV protection.

Increases scratch resistance.

Enhanced appearance.

Restores hydrophobic properties.



MS Schippers

WWW.SCHIPPERSUSA.COM
WWW.DOYOUVEINFOAMBRO.COM

5.4cm x 5.4cm x 25cm

5.4cm

5.4cm

25cm



UV PROTECTION

SURFACE PROTECTION

ULTRA HYDROPHOBIC

HYPER GLOSS

PROLONG

CERAMIC MAINTENANCE SPRAY



PRODUCT INFORMATION

Prolong's real SiO2 matrixes form as the siloxanes cure on the surface. SiO2 should never be found on the ingredient list of ceramic coatings as a standalone component.

Prolong was designed to form a sacrificial layer on the surface of our other T&T Protect professional ceramic coatings, adding enhanced gloss and restoring the hydrophobic properties of the base coatings.

With proper use after each season, Prolong will ensure years of performance from Paint Pro, Paint Pro XD and Glass Pro ceramic coating products.

APPLICATION INSTRUCTIONS



Wash and completely dry all the surfaces.



Spray Prolong directly on the surface or microfiber cloth and wipe onto the area with a circular motion. Immediately after application, using a dry microfiber towel, gently buff the surface until dry and clear.



Keep the surface dry for 12 hours. Do not wash the surface for seven days.

Specially designed and formulated for agriculture and construction equipment by Schippers USA in Davenport, IA.

WWW.SCHIPPERSUSA.COM
WWW.DOYOUVEENFOAMBRO.COM

PROLONG

CERAMIC MAINTENANCE SPRAY



PROTECT
NANOCERAMIC TECHNOLOGY

REAL
SiO2
TECHNOLOGY



MS Schippers

MS Schippers

MS Schippers

MS Schippers